

CLAIR LIGHTING

Professional

Commercial

Architecture



Model : CL Fresnel Spot Color (RGLAC)

400W R/G/B/L/A/C 6-color manual, electric integrated zoom spotlight

Optics

Light source 400W R/G/B/L/A/C six-in-one
Color temperature 2000K-12000K, full color

Color rendering index CRI > 93, R9 > 90

Light source life 50,000 hours

Beam angle 15°~50°

Optical lens: imported threaded lens, soft and uniform light quality, high light output

Effect

Zoom 15°~50°

Focus manual + electric integrated focus

Dimming 4 types of dimming curves control

Control method DMX512/RDM/wireless/APP control

DMX channel 6/9/13 channel

Display LCD

power supply

Input voltage and frequency 100 - 240 VAC, 50/60 Hz

Machine power 400W

Power factor 0.95

Working environment -10°C~45°C

Heat dissipation Copper tube radiator system plus silent fan

Function

Manual zoom, electric zoom

Dimming: 0-100% linear adjustment

Color saturation: can mix any color

PWM frequency is adjustable, suitable for all cameras

physical properties

Dimensions: 340x220x320mm

Weight 10.2kg

Shell die-cast aluminum, high-grade grey paint

Components Power cord, color chip holder, light barrier

Noise: ≤25dB